

STAMFORD

S0L2-K1 Winding 05 / 705

S0L2-K1 - Technical Data Sheet

Standards

Stamford industrial alternators meet the requirements of IEC EN 60034 and the relevant section of other international standards such as BS5000, VDE 0530, NEMA MG1-32, IEC34, CSA C22.2-100 and AS1359. Other standards and certifications can be considered on request.

Quality Assurance

Alternators are manufactured using production procedures having a quality assurance level to BS EN ISO 9001.



Excitation and Voltage Regulators

Excitation System	
AVR Type	AVR Power
AS540	Self-Excited / Aux winding
Voltage Regulation	± 1%
No Load Excitation Voltage (V)	12 V
Full Load Excitation Voltage (V)	48 V

STAMFORD®

S0L2-K1 Winding 05 / 705

Electrical Data		
Insulation System	Class H	
Stator Winding	Double Layer Concentric	
Winding Pitch	Two Thirds	
Winding Leads	4	
Winding Number	05 / 705	
Number of Poles	4	
IP Rating	IP23	
RFI Suppression	EN 61000-6-2 & EN 61000-6-4, refer to factory for others	
Waveform Distortion	NO LOAD < 2.5% NON-DISTORTING BALANCED LINEAR LOAD < 5.0%	
Short Circuit Ratio	1/Xd	
Steady State X/R Ratio	3.1	
50 Hz		
Telephone Interference	THF < 2%	
Voltage Series	230	230
Power Factor	0.8	1.0
kVA Base Rating (Class H)	15	16.2
Saturated Values in Per Unit at Base Ratings and Voltages		
Xd Dir. Axis Synchronous	1.519	1.641
X'd Dir. Axis Transient	0.164	0.177
X''d Dir. Axis Subtransient	0.149	0.161
Xq Quad. Axis Reactance	1.103	1.191
X''q Quad. Axis Subtransient	0.211	0.228
XL Stator Leakage Reactance	0.093	0.100
X2 Negative Sequence Reactance	0.275	0.297
X0 Zero Sequence Reactance	0.094	0.102
Unsaturated Values in Per Unit at Base Ratings and Voltages		
Xd Dir. Axis Synchronous	2.020	2.182
X'd Dir. Axis Transient	0.189	0.204
X''d Dir. Axis Subtransient	0.174	0.188
Xq Quad. Axis Reactance	1.136	1.227
X''q Quad. Axis Subtransient	0.253	0.273
XL Stator Leakage Reactance	0.105	0.113
X2 Negative Sequence Reactance	0.330	0.356
X0 Zero Sequence Reactance	0.110	0.119
Time Constants (Seconds)		
T'd TRANSIENT TIME CONST.	0.035	
T''d SUB-TRANSTIME CONST.	0.002	
T'do O.C. FIELD TIME CONST.	0.58	
Ta ARMATURE TIME CONST.	0.016	

STAMFORD®

S0L2-K1 Winding 05 / 705



Resistances in Ohms (Ω) at 22°C	
Stator Winding Resistance (Ra)	0.185 Ω per phase series connected
Rotor Winding Resistance (Rf)	0.703 Ω
Exciter Stator Winding Resistance	14.624 Ω
Exciter Rotor Winding Resistance	0.135 Ω per phase
Positive Sequence Resistance (R1)	0.231 Ω
Negative Sequence Resistance (R2)	0.266 Ω
Zero Sequence Resistance (R0)	0.231 Ω
Aux Winding Resistance (with winding 705 only)	4.042 Ω
Mechanical data	
Cooling Air	0.105 m ³ /sec (50Hz)
Shaft and Keys	All alternator rotors are dynamically balanced to better than BS6861: Part 1 Grade 2.5 for minimum vibration in operation.
Bearing	Single Bearing
Weight Complete Alternator	113.0 kg
Weight Wound Stator	45.4 kg
Weight Wound Rotor	40.0 kg
Moment of Inertia	0.145 kgm ²
Shipping weight in a Crate	151 kg
Packing Crate Size	930X590X760 mm
Maximum Over Speed	2250 RPM for two minutes
Bearing Drive End	N/A
Bearing Non-Drive End	Ball Bearing, 6305-2RS1

STAMFORD

S0L2-K1 Winding 05 / 705

Single Phase Efficiency Curves

50Hz




STAMFORD

S0L2-K1 Winding 05 / 705

Locked Rotor Motor Starting Curves

50Hz




Transient Voltage Dip Scaling Factor		Transient Voltage Rise Scaling Factor
PF	Factor	For voltage rise multiply voltage dip by 1.25
< 0.5	1.00	
0.5	0.97	
0.6	0.93	
0.7	0.90	
0.8	0.85	
0.9	0.83	
1.0	0.80	

STAMFORD

S0L2-K1 Winding 705

Short Circuit Decrement Curve

*Note: Applicable only for Winding 705 (Auxiliary winding).
Winding 05 (no Auxiliary winding) will not provide short circuit capability.*




Sustained Short Circuit = 196 Amps

STAMFORD

S0L2-K1 Winding 05 / 705

Typical Alternator Operating Chart



STAMFORD®

S0L2-K1 Winding 05 / 705

RATINGS AT 0.8/1.0 POWER FACTOR

Class - Temp Rise	Standby - 163/27°C	Standby - 150/40°C	Cont. H - 125/40°C	Cont. F - 105/40°C
50 Series (V)	230 230	230 230	230 230	230 230
Hz Power Factor	0.8 1.0	0.8 1.0	0.8 1.0	0.8 1.0
kVA	16.5 17.8	16.0 17.3	15.0 16.2	13.7 14.7
kW	13.2 17.8	12.8 17.3	12.0 16.2	11.0 14.7
Efficiency (%)	79.2 83.1	79.6 83.4	80.5 84.2	81.4 85.1
kW Input	16.7 21.4	16.1 20.7	14.9 19.2	13.5 17.3

De-Rates

All values tabulated above are subject to the following reductions:

- 3% for every 500 meters by which the operating altitude exceeds 1000 meters above mean sea level
- 3% for every 5°C by which the operational ambient temperature exceeds 40°C
- For any other operating conditions impacting the cooling circuit please refer to applications

Note: Requirement for operating in an ambient exceeding 60°C and altitude exceeding 4000 meters must be referred to applications.

Dimensional and Torsional Drawing

For dimensional and torsional information please refer to the alternator General Arrangement and rotor drawings available on our website (<http://stamford-avk.com/>)

Note: Continuous development of our products means that the information contained in our data sheets can change without notice, and specifications should always be confirmed with Cummins Generator Technologies prior to purchase.



Follow us @stamfordavk



Cummins Generator Technologies



View our videos at youtube.com/stamfordavk

news.stamford-avk.com

For Applications Support:
applications@cummins.com

For Customer Service:
service-engineers@stamford-avk.com

For General Enquiries:
info@cumminsgeneratortechnologies.com

Copyright 2016. Cummins Generator Technologies Ltd. All rights reserved.
Cummins and the Cummins logo are registered trade marks of Cummins Inc.
STAMFORD is a registered trade mark of Cummins Generator Technologies Ltd.

